

S.A.T. SOLUTIONS

www.serviciotecnico-sat.com.ar

Tel: 4307-0901 Cel: 1557001119

Servicio Técnico Especializado

Servicio Tecnico Tv Digital

S.A.T. Solutions

KIT SEGURIDAD 4 CANALES + 4 CAMARAS + HD500G

\$ 0.00

KIT SEGURIDAD 4 CANALES + 4 CAMARAS + HD500G

type=image,width=52.6355,height=32.269
149.20 0 0 91.47 28.35 323.32
cm /I2 Do Q

ï¿½ï¿½ï¿½type=image,width=52.6355,height=32.0045ï¿½ï¿½ï¿½
149.20 0 0 90.72 28.35 324.07
cm /l3 Do Q

type=image,width=52.6355,height=32.0045
149.20 0 0 90.72 28.35 324.07
cm /14 Do Q

ï¿½ï¿½ï¿½type=image,width=52.1065,height=31.74ï¿½ï¿½ï¿½q
147.70 0 0 89.97 28.35 324.82
cm /l5 Do Q

type=image,width=52.6355,height=32.0045
149.20 0 0 90.72 28.35 324.07
cm /l6 Do Q

ï¿½ï¿½ï¿½type=image,width=53.6935,height=32.798ï¿½ï¿½ï¿½q
152.20 0 0 92.97 28.35 321.82
cm /l7 Do Q

*La tecnologÃ­a de compresiÃ³n H.264

*Soporta D1 grabaciÃ³n y reproducciÃ³n

- *Interfaz de usuario avanzada y amigable con el control del ratón USB
- *Soporta la reproducción de varios canales simultáneos con el navegador IE de los videos *grabados en distintos marcos temporales
- *Vigilancia total en línea a través de IE / Safari navegador de video remoto y audio en vivo *vista, reproducción, configuración, backup y archivo
- *Incorporado en el puerto RS-485 para control PTZ
- *Función de pre-grabación que permite que las imágenes adicionales para ser capturados antes *de la detección de movimiento de eventos
- *Notificación por correo electrónico al instante para eventos activada por alarma
- *Soporta sincronización de reloj con NTP
- *Se puede ver en pantalla ancha LCD
- *Modo de pantalla cuádruple, individual y PIP (Picture-In-a-Picture) para la visualización en vivo
- *Autorización de usuarios y de autenticación
- *Máscaras de privacidad para la protección del área privada (máx. 4 zonas por canal)
- *Series KView descargable gratuito para el monitoreo y control remoto a través de iPhone, *iPad y dispositivos portátiles Android
- *Interfaz USB 2.0 para facilitar el backup
- *KGUARD Servicio DDNS (kguard.org) incluido

NS401-4CW214H Specifications

| | |
|--------------|--------------------------------|
| Model No. | NS401-4CW214H |
| Product Name | 4CH DVR Kit with 4 CCD Cameras |

Standalone DVR Specifications

| | |
|-------|-------|
| Model | NS401 |
|-------|-------|

| | |
|-----------------------------------|---|
| Video Format | NTSC / PAL |
| Operating System | LINUX |
| Video | |
| Input / Output | 4 BNC Inputs /1 VGA Output, 2 BNC Outputs |
| Video Compression | H.264 |
| Audio | |
| Input / Output | 1 RCA Input / 1RCA Output |
| Display | |
| Resolution | NTSC: 704x480 / PAL: 704x576 |
| Frame Rate | NTSC: 120fps / PAL: 100fps |
| Recording | |
| Resolution | NTSC: CIF(352x240) / HD1(704x240) / D1(704x480) PAL: CIF(352x288) / HD1(704x288) / D1(704x576) |
| Frame Rate | NTSC: 120fps-CIF / 120fps-HD1 / 120fps-D1 PAL: 100fps-CIF / 100fps-HD1 / 100fps-D1 |
| Modes | Always / Schedule / Motion Detection / Remote Recording |
| HDD | |
| Interface | 1 SATA Fixed HDD Rack |
| Capacity | Up to 2TB |
| Playback | |
| Search | Time & Date / Event List / Time Bar |
| Channel | Max. 4CH Simultaneous Playback / Network 4CH |
| Mode | Play, Fast Forward, Fast Rewind, Frame by Frame |
| Network | |
| Network Interface | RJ45, 10M/100M, Supports TCP/IP, DHCP,DDNS, PPPoE |
| Network Function | IE and Safari Browser Supported |
| General | |
| USB Interface | USB for Mouse and File Backup |
| PTZ Control | Built-in RS-485 / supports PELCO-P & PELCO-D |
| Sensor & Alarm I/O | N/A |
| Backup | USB to Flash Drive / Network |
| Power Supply | DC12V / 2A |
| Working Temperature | -10Â°C ~ 50Â°C (14Â°F~122Â°F) |
| Storage Temperature | -20Â°C ~ 70Â°C (-4Â°F~158Â°F) |
| Working Humidity | 10%~90% |
| CCTV Camera Specifications | |
| Model No. | CW214H |
| Video | |
| Image Sensor | 1/4" SHARP Color CCD |
| Effective pixels - NTSC | 512(H) x 492(V) |
| Effective pixels - PAL | 500(H) x 582(V) |
| Electronics Shutter NTSC | 1/60-1/120,000(sec) |
| Electronics Shutter PAL | 1/50-1/120,000(sec) |
| Horizontal Resolution | 420 TV Lines |
| Lens | 3.6mm Fixed |
| View Angle | 65 Degrees |
| Video Output | 1.0VP-P, 75Î© |
| S/N Ratio | More than 52dB ^{1/4} AGCOFFI ^{1/4} ‰ |

| | |
|-------------------------|---|
| Day / Night Mode | Color during day / switches to B&W at night |
| Minimum Illumination | While Infrared LED ON "0" lux |
| Gain Control | Auto |
| Backlight Compensation | Auto |
| Night Vision | |
| Night Vision Distance | Up to 20M / 65ft. |
| Number of Infra-Red LED | 24 pcs |
| Infra-Red Wavelength | 850 mm |
| Infra-Red LED Life | 10,000 hrs |
| General | |
| Indoor / Outdoor | Weatherproof(Both) |
| Operating Temperature | -10Â° ~ 50Â°C (14Â°F~122Â°F) |
| Storage Temperature | -20Â° ~ 70Â°C (-4Â°F~158Â°F) |
| Camera Dimension | L179xW65xH63 |
| Body Construction | Aluminum |

NS401-4CW214H Package

NS401
 Power Adapter
 RCA to BNC Cable
 Remote Control
 USB Mouse
 Software CD
 Quick Guide
 Power Cord
 Camera
 Slim Cable
 Screw Kit
 4-Way Split Power Cable
 Camera Quick Guide
 Power Adapter
 Position Gasket

[Informaci3n](#)